

Primax

Synonymous with function and performance, enter the Primax, the new era of high intensity illumination in LED. With its high flux output and high luminous intensity, Primax transcends today LED lightings technology and how we perceive it. The small package outline (3.7 x 3.5 x 0.8 mm) and high intensity make it an ideal choice for backlighting, signage, exterior automotive lighting and decorative lighting.

Features:

- > Super high brightness surface mount LED
- > 120° viewing angle.
- > Compact package outline (LxW) of 3.7 x 3.5 mm.
- > Ultra low height profile - 0.8mm.
- > Low thermal resistance.
- > Compatible to IR reflow soldering.
- > Environmental friendly; RoHS compliance.
- > Superior corrosion resistance.
- > Compliance to automotive standard; AEC-Q102.

Applications:

- > Automotive Application: Turn Signal, Side Marker.



Optical Characteristics at Tj=25°C

Part Number	Color	Viewing Angle°	Luminous Flux @ 150mA (lm) <i>Appx. 1.2</i>		
			Min.	Typ.	Max.
● MAZY-PZHG-QR3-1	InGaN Yellow	120	30.6	39.8	51.7
● Not for new design					


Electrical Characteristics at Tj=25°C

Part Number	Vf @ If = 150mA <i>Appx. 3.1</i>		
	Min. (V)	Typ. (V)	Max. (V)
MAZY-PZHG	2.70	3.00	3.20

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	300	mA
Peak pulse current (T _s =55°C, tp ≤ 100µs, Duty cycle = 0.03)	400	mA
Reverse voltage	Not designed for reverse bias	V
ESD threshold (HBM)	8	kV
LED junction temperature	150	°C
Operating temperature	-40 ... +125	°C
Storage temperature	-40 ... +125	°C
Thermal resistance (Rated current = 150mA, Ts=25°C)		
- Real Thermal Resistance		
Junction / solder point, R _{th JS real} (typ = 20)	25	K/W
- Electrical Thermal Resistance		
Junction / solder point, R _{th JS el} (typ = 14)	18	K/W

MAZY-PZHG, Color Grouping *Appx. 2.1*



Bin		1	2	3	4
F	Cx	0.5606	0.5705	0.5883	0.5780
	Cy	0.4250	0.4289	0.4111	0.4110

InGaN wavelength is very sensitive to drive current. Operating at lower current is not recommended and may yield unpredictable performance current pulsing should be used for dimming purposed.

Luminous Flux Group at Tj=25°C

Brightness Group	Luminous Flux (lm) <i>Appx. 1.2</i>
Q2	30.6 ... 34.8
Q3	34.8 ... 39.8
R2	39.8 ... 45.2
R3	45.2 ... 51.7


Vf Binning (Optional)

Vf Bin @ 150mA	Forward Voltage (V) <i>Appx. 3.1</i>
VM6	2.70 ... 3.00
VM7	3.00 ... 3.30

Please consult sales and marketing for special part number to incorporate Vf binning.


Relative Luminous Flux Vs Forward Current Appx. 4.1

$$\Phi_v/\Phi_v(150\text{mA}) = f(I_F); T_j = 25^\circ\text{C}$$




Forward Current Vs Forward Voltage Appx. 4.1

$$I_F = f(V_F); T_j = 25^\circ\text{C}$$




Maximum Current Vs Temperature

$$I_F = f(T)$$




Relative Spectral Emission Appx. 4.1

$$\Phi_{rel} = f(\lambda); T_j = 25^\circ\text{C}; I_F = 150\text{mA}$$




Chromaticity Coordinate Shift Vs Forward Current Appx. 4.1

$$\Delta Cx, \Delta Cy = f(I_F); T_j = 25^\circ\text{C}$$




Allowable Forward Current Vs Duty Ratio

$$(T_s = 55^\circ\text{C}; t_p \leq 100\mu\text{s})$$




Radiation Pattern Appx. 4.1




Forward Voltage Vs Junction Temperature Appx. 4.1

$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 150\text{mA}$$




Relative Luminous Flux Vs Junction Temperature Appx. 4.1

$$\Phi_V/\Phi_V(25^\circ\text{C}) = f(T_j); I_F = 150\text{mA}$$




Chromaticity Coordinate Shift Vs Junction Temperature Appx. 4.1

$$\Delta Cx, \Delta Cy = f(T_j); I_F = 150\text{mA}$$




PrimaxPlus • InGaN MAZY-PZHG Package Outlines Appx. 5.1




Material

Material	
Lead-frame	Cu Alloy With Au Plating
Package	High Temperature Resistant Plastic
Encapsulant	Silicone Resin
Soldering Leads	Au Plating



Recommended Solder Pad *Appx. 5.1*



Taping and orientation *Appx. 5.1*



Packaging Specification




	Reel Diameter (mm)	Quantity (pcs)	*Ordering Number
Standard Packing	180	1500	MAZY-PZHG-xxx-x
Optional Packing	329	5000	MAZY-PZHG-xxx-x-5

Notes:

* For ordering purpose only. Please consult sales and marketing for details.


Packaging Specification



Quantity per bag (pcs)	Average 1pc PrimaxPlus (g)	1 completed bag (g)
1500	0.034	245 ± 10
5000	0.034	1150 ± 10

Recommended Pb-free Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E



Profile Feature	Symbol	Min.	Pb-Free Assembly			Unit
			Recommended	Max.		
Ramp-up rate to preheat 25°C to T_{smin}	-	-	2	3		°C/s
Time t_s T_{smin} to T_{smax}	t_s	60	100	120		s
Ramp-up rate to peak T_L to T_p	-	-	2	3		°C/s
Liquidous temperature	T_L	-	217	-		°C
Time above liquidous temperature	t_L	60	80	150		s
Peak temperature	T_p	-	245	260		°C
Time within 5°C of the specified peak temperature $T_p - 5^\circ\text{C}$	t_p	10	20	30		s
Ramp-down rate T_p to 100°C	-	-	3	6		°C/s
Time 25°C to T_p	-	-	-	480		s

Appendix

1) **Brightness:**

- 1.1 Luminous intensity is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.2 Luminous flux is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.3 Radiant intensity is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.4 Radiant flux is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).

2) **Color:**

- 2.1 Chromaticity coordinate groups are measured at current pulse 25 ms(typ) with an internal reproducibility of ± 0.005 and an expanded uncertainty of ± 0.01 (accordingly to GUM with a coverage factor of $k=3$).
- 2.2 Dominant wavelength is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 0.5\text{nm}$ and an expanded uncertainty of $\pm 1\text{nm}$ (accordingly to GUM with a coverage factor of $k=3$).

3) **Voltage:**

- 3.1 Forward Voltage, V_f is measured when a current pulse of 8 ms(typ) with an internal reproducibility of $\pm 0.05\text{V}$ and an expanded uncertainty of $\pm 0.1\text{V}$ (accordingly to GUM with a coverage factor of $k=3$).

4) **Typical Values:**

- 4.1 Due to the specific conditions of semiconductor devices' manufacturing processes, the provided typical data and calculated correlations of technical parameters should only be considered as statistical values. It is important to note that the actual parameters of individual devices may deviate from these typical data, calculated correlations or the typical characteristic line. Dominant reserves the right to update this typical data without prior notice, particularly in response to technical enhancements.

5) **Tolerance of Measure**

- 5.1 Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimension are specified in mm.

Revision History

Page	Subjects	Date of Modification
-	Initial Release	31 Jul 2019
1, 3	Update Product Photo Update OEM Spec	08 Jan 2020
10, 11, 12	Update Packaging Specification	04 Mar 2020
5, 6, 9, 12	Update Graph: Relative Forward Voltage Vs Junction Temperature, Relative Luminous Flux Vs Junction Temperature, Chromaticity Coordinate Shift Vs Junction Temperature Add Polarity in Taping and Orientation Update Recommended Pb-free Soldering Profile	27 Oct 2021
3	Typo Error on Color Box Naming	18 Mar 2022
10, 11	Update Quantity per Reel: 1000pcs to 1500pcs	01 Nov 2023
2, 11	Not for New Design: MAZY-PZHG-QR3-1 Update Packaging Specification	16 Jul 2026

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Opto Technologies does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Opto Technologies reserves the right to make changes to any products in order to improve reliability, function or design.

DOMINANT Opto Technologies products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Opto Technologies.

Dispose of product is in accordance with local, regional, national and international regulations.

About Us

DOMINANT Opto Technologies is a dynamic company that is amongst the world's leading automotive LED manufacturers. With an extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing and development capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Opto Technologies, an IATF 16949 and ISO 14001 certified company, can be found under <http://www.dominant-semi.com>.

Please contact us for more information:

DOMINANT Opto Technologies Sdn. Bhd
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia.
Tel: +606 283 3566 Fax: +606 283 0566
E-mail: sales@dominant-semi.com