

SpicePlus

Like spice, its diminutive size is a stark contrast to its standout performance in terms of brightness, durability and reliability. Despite being the smallest in size yet the SpicePlus packs a powerful performance and is a highly reliable design device.



Features:

- > Super high brightness surface mount LED automotive exterior applications.
- > 120° viewing angle.
- > Compact package outline (LxW) of 2.5 x 2.0mm.
- > Ultra low height profile - 0.7mm.
- > Low thermal resistance.
- > Superior corrosion robustness.
- > Compatible to IR reflow soldering.
- > Compliance to automotive standard; AEC-Q102.
- > Environmental friendly; RoHS compliance.



Applications:

- > Automotive: Exterior application: eg: Turn Signal, Rear Combination Light (RCL), Center High Mounted Stop Light (CHMSL).

Optical Characteristics at Tj=25°C

Part Number	Color	Viewing Angle°	Luminous Flux @ 50mA (lm) <i>Appx. 1.2</i>		
			Min.	Typ.	Max.
SVS-ASS-G3J2-3	Super Red, 635 nm	120	4.20	5.50	7.15
SVS-ASS-H3K2-2	Super Red, 630 nm	120	5.50	7.15	9.35
SVA-ASS-KL3-4	Amber, 625 nm	120	8.20	10.70	13.90
SVA-ASS-K3M2-2	Amber, 617 nm	120	9.35	12.20	15.80
SVY-ASS-K3M2-4	Yellow, 592 nm	120	9.35	12.20	15.80
SVY-ASS-KL3-3	Yellow, 589 nm	120	8.20	10.70	13.90
SVY-ASS-J3L2-2	Yellow, 586 nm	120	7.15	9.35	12.20

Electrical Characteristics at Tj=25°C

Part Number	Vf @ If = 50mA <i>Appx. 3.1</i>			Vr @ Ir = 10uA <i>Appx. 7.1</i>
	Min. (V)	Typ. (V)	Max. (V)	Min. (V)
SVx-ASS (except Yellow)	1.90	2.20	2.65	12
SVY-ASS	1.90	2.35	2.65	12

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	70	mA
Peak pulse current; (Ts = 55°C, tp ≤ 100µs, Duty cycle = 0.03)	400	mA
Reverse voltage <i>Appx. 7.1</i>	12	V
ESD threshold (HBM)	2	KV
LED junction temperature	135	°C
Operating temperature	-40 ... +115	°C
Storage temperature	-40 ... +125	°C
Thermal resistance (Rated current = 50mA, Ts = 25 °C)		
- Real Thermal Resistance Junction / solder point, R _{th JS real}		
Super Red & Amber (typ = 25)	45	K/W
Yellow (typ = 27)	50	K/W
- Electrical Thermal Resistance Junction / solder point, R _{th JS el}		
Super Red & Amber (typ = 17)	30	K/W
Yellow (typ = 23)	40	K/W

Wavelength Grouping at Tj= 25°C

Color	Group	Wavelength distribution (nm) <i>Appx. 2.2</i>
SVx; Super Red	Full	627 - 637
	W	627 - 630
	X	630 - 633
	Y	633 - 637
SVx; Amber	Full	612 - 627
	W	612 - 616
	X	616 - 620
	Y	620 - 624
	Z	624 - 627
SVx; Yellow	Full	583 - 595
	W	583 - 586
	X	586 - 589
	Y	589 - 592
	Z	592 - 595

Luminous Flux Group at Tj=25°C

Brightness Group	Luminous Flux <i>Appx. 1.2</i> (lm)
G3	4.20 ... 4.90
H2	4.90 ... 5.50
H3	5.50 ... 6.30
J2	6.30 ... 7.15
J3	7.15 ... 8.20
K2	8.20 ... 9.35
K3	9.35 ... 10.70
L2	10.70 ... 12.20
L3	12.20 ... 13.90
M2	13.90 ... 15.80


Vf Binning (Optional)

Vf Bin @ 50 mA	Forward Voltage (V) <i>Appx. 4.1</i>
V43	1.90 ... 2.05
V44	2.05 ... 2.20
V45	2.20 ... 2.35
V46	2.35 ... 2.50
V47	2.50 ... 2.65

Please consult sales and marketing for special part number to incorporate Vf binning.


Relative Luminous Flux Vs Forward Current Appx. 4.1

$$\Phi_v/\Phi_v(50\text{mA}) = f(I_F); T_j = 25^\circ\text{C}$$




Forward Current Vs Forward Voltage Appx. 4.1

$$I_F = f(V_F); T_j = 25^\circ\text{C}$$




Maximum Current Vs Temperature

$$I_F = f(T)$$




Relative Spectral Emission Appx. 4.1

$$\Phi_{rel} = f(\lambda); T_j = 25^\circ\text{C}; I_F = 50\text{mA}$$




Allowable Forward Current Vs Duty Ratio

$$(T_s = 55^\circ\text{C}; t_p \leq 100\mu\text{s})$$




Radiation Pattern Appx. 4.1




Forward Voltage Vs Junction Temperature *Appx. 4.1*

$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 50\text{mA}$$




Relative Luminous Flux Vs Junction Temperature *Appx. 4.1*

$$\Phi_V/\Phi_V(25^\circ\text{C}) = f(T_j); I_F = 50\text{mA}$$




Wavelength Vs Junction Temperature *Appx. 4.1*

$$\Delta \lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25^\circ\text{C}) = f(T_j); I_F = 50\text{mA}$$




SpicePlus 2520 AllnGaP: SVx-ASS Package Outlines *Appx. 5.1*




Material

Material	
Lead-frame	Cu Alloy With Ag Plating
Package	High Temperature Resistant Plastic
Encapsulant	Epoxy Resin
Soldering Leads	Sn Plating



Recommended Solder Pad *Appx. 5.1*



Taping and orientation Appx. 5.1



Packaging Specification




	Reel Diameter (mm)	Quantity (pcs)	*Ordering Number
Standard Packing	180	4000	SVx-ASS-xxx-x
Optional Packing	260	8000	SVx-ASS-xxx-x-8

Notes:

* For ordering purpose only. Please consult sales and marketing for details.


Packaging Specification



Quantity per bag (pcs)	Average 1pc SpicePlus 2520 (g)	1 completed bag (g)
4000	0.0089	150 ± 10
8000	0.0089	360 ± 10

Recommended Pb-free Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E



Profile Feature	Symbol	Min.	Pb-Free Assembly		Unit
			Recommended	Max.	
Ramp-up rate to preheat 25°C to T_{smin}	-	-	2	3	°C/s
Time t_s T_{smin} to T_{smax}	t_s	60	100	120	s
Ramp-up rate to peak T_L to T_p	-	-	2	3	°C/s
Liquidous temperature	T_L	-	217	-	°C
Time above liquidous temperature	t_L	60	80	150	s
Peak temperature	T_p	-	245	260	°C
Time within 5°C of the specified peak temperature $T_p - 5^\circ\text{C}$	t_p	10	20	30	s
Ramp-down rate T_p to 100°C	-	-	3	6	°C/s
Time 25°C to T_p	-	-	-	480	s

Appendix

1) **Brightness:**

- 1.1 Luminous intensity is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.2 Luminous flux is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.3 Radiant intensity is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.4 Radiant flux is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).

2) **Color:**

- 2.1 Chromaticity coordinate groups are measured at current pulse 25 ms(typ) with an internal reproducibility of ± 0.005 and an expanded uncertainty of ± 0.01 (accordingly to GUM with a coverage factor of $k=3$).
- 2.2 Dominant wavelength is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 0.5\text{nm}$ and an expanded uncertainty of $\pm 1\text{nm}$ (accordingly to GUM with a coverage factor of $k=3$).

3) **Voltage:**

- 3.1 Forward Voltage, V_f is measured when a current pulse of 8 ms(typ) with an internal reproducibility of $\pm 0.05\text{V}$ and an expanded uncertainty of $\pm 0.1\text{V}$ (accordingly to GUM with a coverage factor of $k=3$).

4) **Typical Values:**

- 4.1 Due to the specific conditions of semiconductor devices' manufacturing processes, the provided typical data and calculated correlations of technical parameters should only be considered as statistical values. It is important to note that the actual parameters of individual devices may deviate from these typical data, calculated correlations or the typical characteristic line. Dominant reserves the right to update this typical data without prior notice, particularly in response to technical enhancements.

5) **Tolerance of Measure**

- 5.1 Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimension are specified in mm.

6) **Corrosion Robustness:**

- 6.1 Test conditions: $40^\circ\text{C} / 90\% \text{ rh} / 15 \text{ ppm H}_2\text{S} / 336 \text{ h}$.
= Stricter than IEC 60068-2-43 (H_2S) [$25^\circ\text{C} / 75\% \text{ rh} / 10 \text{ ppm H}_2\text{S} / 21 \text{ days}$].

7) **Reverse Voltage:**

- 7.1 Not designed for reverse operation. Continuous reverse voltage can cause migration and LED damage.

8)

- 8.1 Package edge may have plastic burr or protrusion no bigger than 0.05mm.

Revision History

Page	Subjects	Date of Modification
-	Initial Release	23 Jun 2021
2	Update Rth Max	02 Mar 2022
8	Add Polarity in Package Outline	11 Aug 2022
2, 6, 7	Update Electrical Characteristics Update Graph: Relative Luminous Flux Vs Forward Current Update Graph: Forward Current Vs Forward Voltage Update Graph: Forward Voltage Vs Junction Temperature	16 Feb 2023
11, 12	Update Optional Packing	01 Nov 2024
1, 8	Update Product Photo Update Package Outline	11 Feb 2026

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Opto Technologies does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Opto Technologies reserves the right to make changes to any products in order to improve reliability, function or design.

DOMINANT Opto Technologies products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Opto Technologies.

Dispose of product is in accordance with local, regional, national and international regulations.

About Us

DOMINANT Opto Technologies is a dynamic company that is amongst the world's leading automotive LED manufacturers. With an extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing and development capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Opto Technologies, an IATF 16949 and ISO 14001 certified company, can be found under <http://www.dominant-semi.com>.

Please contact us for more information:

DOMINANT Opto Technologies Sdn. Bhd
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia.
Tel: +606 283 3566 Fax: +606 283 0566
E-mail: sales@dominant-semi.com